Training and Evaluation Outline Report

Status: Approved 14 Apr 2021 Effective Date: 14 Apr 2021

Task Number: 05-PLT-5215

Task Title: Install a Coupled Pipeline

Distribution Restriction: Approved for public release; distribution is unlimited.

Destruction Notice: None

Foreign Disclosure: FD1 - This training product has been reviewed by the training developers in coordination with the MSCoE, Ft. Leonard Wood, MO 65473 foreign disclosure officer. This training product can be used to instruct international military students from all approved countries without restrictions.

Supporting Reference(s):

Step Number	Reference ID	Reference Name	Required	Primary	Source Information
	ATP 3-34.40	General Engineering (http://armypubs.army.mil/doctrine/DR_pubs /dr_a/pdf/atp3_34x40.pdf)	Yes	Yes	
	ATP 4-43	Petroleum Supply Operations	Yes	No	
	ATP 5-19	RISK MANAGEMENT, with change 1 dated 8 Sep 2014	Yes	No	
	TM 3-34.70	Plumbing, Pipe Fitting, and Sewerage	Yes	No	

Conditions: The element is directed to install a coupled pipeline along a sector of pipeline trace from the fuel source to the Tactical Petroleum Terminal (TPT) in accordance with plans, specifications and Tactical Standing Operating Procedures (TACSOP). All required tools, specialized pipeline equipment, materials and transportation are available. The sector has been cleared and staked. There is an established pipe staging yard with dedicated loading crew, trucks and trailers. Work site security is provided.

Note: The Commander must still determine at what level of training they would want the element to perform. Crawl, walk or run. This can only be determined after consideration as to the units training level.

The Commander prior to evaluating an element in the conduct of the task must determine if it will be conducted in a Live, Virtual, or Constructive environment, additionally it must also be determined which condition as described below that the element will conduct the task. The selection made for this task is at a trained level of proficiency. The commander must determine which of the environments below will best suit the unit and the proficiency level at which the unit is. When conducting crawl or walk level training units should not increase the intensity until the unit has achieved the standards and then unit trainers should include variables that increase proficiency in all conditions.

Note: The condition statement for this task is written assuming the highest training conditions reflected on the Task Proficiency matrix required for the evaluated unit to receive a "fully trained" (T) rating.

Note: Condition terms definitions:

Dynamic Operational Environment: Three or more operational and two or more mission variables change during the execution of the assessed task. Operational variables and threat Tactics, Techniques, and Procedures (TTPs) for assigned counter-tasks change in response to the execution of Blue Forces (BLUFOR) tasks.

Complex Operational Environment: Changes to four or more operational variables impact the chosen friendly COA/mission. Brigade and higher units require all eight operational variables of Political, Military, Economic, Social, Infrastructure, Information, Physical environment, and Time (PMESII-PT) to be replicated in varying degrees based on the task being trained.

Single threat: Regular, irregular, criminal or terrorist forces are present.

Hybrid threat: Diverse and dynamic combination of regular forces, irregular forces, and/or criminal elements all unified to achieve mutually benefiting effects.

This task should not be trained in MOPP 4.

Standards: The element installs a coupled pipeline according to the plans, specifications and TACSOP. The element will conduct test with air, water , or fuel on the pipeline. Couplings, valves and pumping stations should be capable of withstanding pressures of up to 740 pounds per square inch, are leak proof, aligned, and anchored. Task completion should be no later than the time stablished by the directive.

Note: Leaders are defined as the Platoon Leaders, Platoon Sergeants, Squad Leaders, and Team Leaders.

Live Fire: No

Objective Task Evaluation Criteria Matrix:

Plan	an	d Prepare		Ex	ec	ute			Ass	ess
Operationa Environme SQD & PLT	al nt	Training Environment (L/V/C)	Leaders Present at Training/Required	Present at Training/Required	External Eval	Performance Measures	Critical Performance Measures	Leader Performance Measures	Evaluator's Observed Task Proficiency Rating	Commander's Assessment
Dynamic			>=85%	2-909/	Ye	>=91%		>=90%	т	т
(Single Threat)		IA	75-84%	>=80%	S	80- 90%	All	80	T-	T-
Day	W unit CATS statem	65-74%	75-79%		65- 79%		89%	Ρ	Ρ	
Static (Single Threat)		ent.	60-64%	60-74%	No	51- 64%			Р-	P-
			<=59%	<=59%		<=50%	<all< td=""><td><=79%</td><td>U</td><td>U</td></all<>	<=79%	U	U

Remarks: None

Notes: None

Task Statements

Cue: None

DANGER

Suspend all handling of the pipeline system when an electrical storm is within a 5-mile radius of your operation, during high winds, or when your commander notifies you.

Leaders have an inherent responsibility to conduct Risk Management to ensure the safety of all Soldiers and promote mission accomplishment.

WARNING

Be very careful when stringing pipe at night. Soldiers could be injured by a moving truck.

Risk management is the Army's primary decision-making process to identify hazards, reduce risk, and prevent both accidental and tactical loss. All Soldiers have the responsibility to learn and understand the risks associated with this task.

CAUTION

Identifying hazards and controlling risks across the full spectrum of Army functions, operations and activities is the responsibility of all Soldiers.

Performance Steps and Measures

NOTE: Assess task proficiency using the task evaluation criteria matrix.

NOTE: Asterisks (*) indicate leader steps; plus signs (+) indicate critical steps.

STEP/MEASURE G NO-GO N/A Conducts preliminary construction planning. Conducts preliminary construction planning. Conducts preliminary construction planning. Conducts preliminary construction planning. Conducts and tailed project planning. Conducts and planning construction stating areas and delivers materials for each designated sector along the planne trace. Conducts and ppeline components without damaging them as the truck moves along the planne trace. Conducts and ppeline components without damaging them as the truck moves along the planne trace. Conducts are normal/download of thy there conducts during operations. Conducts were normal/download of thy there conducts during operations. Conducts are normal/download of thy there planne trace. Conducts were normal/download of thy there planne trace. Note: Wave are normal/download of thy there planne trace. Note: Note wave scale and there prove that conducts or planne to the planne and expension loops. Conducts are normal/download of thy there planne. Note: Kare and explore or on planne or there are also explore they are needed or or oddring. Conducts and planne compleme to the planne and there are also explore they are needed to conduct during onstruction. Small quantities of loope material neach pipe length an accounting the planne and explore the planne and there are also explore the planne and explore the planne and there are also explore the planne and there are also explore the planne and there planne and there are also the planne and explore the planne and there ar				
	STEP/MEASURE	GO	NO-GO	N/A
	+* 1. The element leader conducts Troop Leading Procedures (TLP).			
b. Requests augmentation support if required.	a. Conducts preliminary construction planning.			
 *2. The element leader conducts detailed project planning. a. Conducts an econnaissance of assigned planing sector if conditions allow. b. Assigns crews and equipment in order to facilitate elificant completion of the project. *3. The element prepares construction staging areas and delivers materials for each designated sector along the pipeline trace. *4. The element conducts stringing operations. *5. The element conducts stringing operations. *6. The element conducts stringing operations. *1. The element order pipeline components from the trucks or trailers. (2) Does not drop pipeline components from the ground. (3) Leaves pipe end caps in place until the pipe is coupled to avoid containnation. b. The crew unloads an extra tubing section for every 60-75 picese. c. The crew places othex valves, gate valves and vents at the specified to avoid them sitting exposed and becoming contaminated with dirt or debins. *6. The element conducts oupling pervations. *6. The element conducts oupling operations. *1. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and from the pipe element. *1. The pipeline coupling crew inspects the pipe sections, coupling stations. Before coupling pipe lengths tiggether, clean any debins through pipe lengths tiggether, clean any debins through pipe lengths tiggether, clean any debins. *1. The element instage popile exclo	b. Requests augmentation support if required.			
	+* 2. The element leader conducts detailed project planning.			
b. Assigns crews and equipment in order to facilitate efficient completion of the project. 4. The element programs construction staging areas and delivers materials for each designated sector along the pipeline trace. 4. The element programs construction staging areas and delivers materials for each designated sector along the pipeline trace. 4. The element programs construction staging areas and delivers materials for each designated sector along the pipeline trace. 4. The element programs construction staging areas and delivers materials for each designated sector along the pipeline trace. 4. The element programs components without damaging them as the truck moves along the pipeline trace. 4. The element conducts stringing operations. 4. The element programs along the ground. 4. The element programs along the ground. 4. The element area ubling section for every 50-75 pices. 4. The element conducts outping pervalues and verts at the specified to avoid committeent of avoid them sitting exposed and becoming contaminated with dirf or debris. 4. The element conducts outping operations. 4. The element conducts outping operations. 4. The pipeline conduing cover inspects the pipe sections, couplings and gaskets for cleanliness and serviceability. 4. The pipeline conduing cover inspects the pipe sections, couplings and gaskets for cleanliness and from the pipe ends. During the pipe lends. 4. The pipeline conducts outping operations. 4. The pipeline conducts outping uperations the pipe lends. 4. The pipeline condult or work outpies the pipe sections, couplings and gaskets for cleanliness and along pipe lends. 4. The element pipe ends. During the material bioled at the purphysic status. 4. The element conducts outping uperation there the pipes will meet. 4. The element conducts outping uperation there the pipes will meet. 4. The element pipe ends. During there along thebring there. 4. The degram pipe pipe pipe lends. 4. The	a. Conducts a reconnaissance of assigned pipeline sector if conditions allow.			
the element coordinates with work site security element before beginning work along the pipeline troc. 4. The element prepares construction staging areas and delivers materials for each designated sector along the pipeline trace. 4. The cerve dworkdask all pipeline components without damaging them as the truck moves along the pipeline trace. (1) Does not drap pipeline components without damaging them as the truck moves along (1) Does not drap pipeline components without damaging them as the truck moves along (1) Does not drap pipeline components without damaging them as the truck moves along (1) Does not drap pipeline components along the ground. (3) Leaver uplaces between subsets and years at the specified to avoid contamination. b. The crew places check valves, gate valves and values at the specified to avoid contamination. b. The origine complex check was, gate valves and values at the specified to avoid contaminates. c. The crew unloads an extra tubing section for every 60-75 pieces. d. The rew unloads an extra tubing section for every 60-75 pieces. d. The origine coupling crew inspects the pipe sections, coupling and gaskets for cleanliness and serviceability. d. The alement conducts coupling orear inspects the pipe sections, coupling and gaskets for cleanliness and serviceability. Note: Keep pipes, valves and verbs clean and fee from dehris during construction. Small quantities of losse material in each pipe length can accurutate in sufficient volume to cleg sand traps or strainers located at the punping stations. Before coupling griee together, clean any debris from the inside and free from dehris during construction. Small quantities of losse material in each pipe length can accurutate in sufficient volume to cleg sand traps or strainers located at the punping stations. d. The dement installs pipeline supports and anged o	b. Assigns crews and equipment in order to facilitate efficient completion of the project.			
+ 4. The element prepares construction staging areas and delivers materials for each designated sector allows and solutions string operations. + 5. The element conducts stringing operations. + 0. The element conducts stringing operations. + 0. The element conducts stringing operations. + 0. The element conducts stringing operations along the ground. (3) Leaves pipe end caps in place until the pipe is coupled to avoid contamination. b. The crew places pipe sections in line, end to end, with a gasket and coupling at each point whare pipe sections meet. • 0. The crew places pipe sections in line, end to end, with a gasket and coupling at each point whare pipe sections meet. • 0. The crew places and stacks of pipe to account for terrain conditions, directional changes and expansion loops. • 0. The crew places and stacks of pipe to account for terrain conditions, directional changes and expansion loops. • 0. The prevent conducts coupling operations. • 1. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for deanniness and serviceability. Note: Keep pipes, valves and verts clean and free from debris during construction. Small quantities of loose material in each pipe lengths the pipeline coupling crew couples the pipe is excitons getter. • 1. The pipeline coupling crew couples the pipe is accline, starting backets for deanniness and serviceability. Note: Keep pipes, valves and verts clean and free from debris during construction. Small quantities of loose material in each pipe lengths the pipe length coupling crew couples the pipeline. (1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling. (2) Places an open, greased goupling under the pipe there, there any debris. (3) Slides a dirfere, greased gasket onto one pipe end (for one-piece gaskets). (b) Lints up the coupling and back thing of the snap-joint coupling brace	+ 3. The element coordinates with work site security element before beginning work along the pipeline trace.			
	+ 4. The element prepares construction staging areas and delivers materials for each designated sector along the pipeline trace.			
+ a. The crew downloads all pipeline components from the trucks or trailers. (1) Does not drop pipeline components from the trucks or trailers. (2) Does not drop pipeline components from the trucks or trailers. (3) Leaves pipe end caps in place until the pipe is coupled to avoid contamination. b. The crew places check values, gate values and vents at the specified locations along the truck. c. The crew unloads an extra tubing section for every 50-75 picess. d. The crew places check values, gate values and vents at the specified locations along the trace. Note: Valves are normally downloaded right before they are needed in order to avoid them sitting exposed and becoming contaminated with dirt or debis. e. The crew places check values, gate values and vents at the specified locations along the trace. Note: Valves are normally downloaded right before they are needed in order to avoid them sitting exposed and becoming contaminated with dirt or debis. e. The crew places check values, gate values couplings and gaskets for cleanliness and serviceability. e. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and from the pipe ends. Do not use damaged or correded pipes. t. The pipeline coupling under the point where the pipes will meet. Note: Turn the coupling under the point where the pipes will meet. Note: Turn the coupling under the point where the pipes gaskets). Note: a gasket over the seam where both pipe acks, lazy board, or wooden blocks placed end to end	+ 5. The element conducts stringing operations.		_	
(1) Does not drap pipeline components from the trucks or trailers.	+ a. The crew downloads all pipeline components without damaging them as the truck moves along the pipeline trace.			
(2) Does not drag pipeline components along the ground. (3) Leaves pipe end caps in place utils the pipe is coupled to avoid contamination. b. The crew places pipe sections in line, end to end, with a gasket and coupling at each point where pipe sections meet. c. The crew unloads an extra tubing section for every 50-75 pieces. c. The crew unloads an extra tubing section for every 50-75 pieces. c. The crew unloads an extra tubing section for every 50-75 pieces. c. The crew unloads an extra tubing section for every 50-75 pieces. c. The crew unloads an extra tubing section for every 50-75 pieces. c. The crew places theore shows and sticks of pipe to account for terrain conditions, directional changes and expansion toops. c. The pipeline coupling operations. c. The pipeline coupling operations. c. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and servicesbilly. c. The pipeline coupling crew inspects the pipe sections, coupling and gaskets and event to avoid them siting exposed and becoming contaminated with dirt of the six de and from the pipe ends. Do not use damaged or corroded pipes. c. The pipeline coupling grews one pipe and (for one-piece gaskets). (1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to dafford ease of coupling. (2) Pise as a nopen, greased coupling under the point where the pipes will meet. Note: Turn the coupling upward to prevent exposure to debris. (3) Sides the gasket tore the seam where both pipe ends to gether. (4) Aligns and joins the ends of both pipe sections together. (5) Closes the coupling and seats is into the bottog morely end gaskets). (6) Lifts up the coupling and anchors. c. The element installs pipeline supports and anchors. c. The element installs pipeline supports and anchors. c. The element performs a hydrostatic test of the pipeline. c. The element pentors and uncher	(1) Does not drop pipeline components from the trucks or trailers.			
(3) Leaves pipe and caps in place until the pipe is coupled to avoid contamination.	(2) Does not drag pipeline components along the ground.			
b. The crew places pipe sections in line, end to end, with a gasket and coupling at each point where pipe sections meet. c. The crew values and extra tubing section for every 50-75 pieces. d. The crew places check valves, gate valves and vents at the specified locations along the trace. Note: Valves are normally downloaded right before they are needed in order to avoid them sitting exposed and becoming contaminated with dit or debis. + 6. The element conducts coupling operations. + 6. The element conducts coupling operations. + 6. The element conducts coupling operations. + 6. The element conducts coupling operations and gaskets for cleanliness and serviceability. Note: Keep pipes, valves and vents clean and free from debris during construction. Small quantities of loose material in each pipe length can accumulate in sold sand traps or strainers loosed at the pumping stations. Before coupling pipe lengths together, clean any debris troe the coupling pipe ends. Do not use damaged or corroded pipes. + b. The pipeline coupling crew couples the pipeline. (1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling upward to prevent exposure to debris. (2) Places an open, greased caupling under the point where the pipes will meet. (3) Slides a dirf-free, greased gasket ton to ne pipe end (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and endors. (7) Closes the coupling halves together completely. (8) The element installs pipeline supports and anchors. (8) The element installs pipeline int	(3) Leaves pipe end caps in place until the pipe is coupled to avoid contamination.			
 c. The crew unleads an extra tubing section for every 50-75 pieces. + d. The crew places check valves, gate valves and vents at the specified locations along the trace. Note: Valves are normally downloaded right before they are needed in order to avoid them sitting exposed and becoming contaminated with dirt or debris. + 6. The element conducts coupling operations. + 6. The element instance or the piece daskets for cleanliness and serviceability. Note: Keep pipes, valves and vents clean and free from debris during construction. Small quantities of locae material in each pipe length can accumulate in sufficient volume to clog sand traps or strainers located at the pumping stations. Before coupling pipe length can accumulate in sufficient volume to clog sand traps or strainers located at the pumping stations. Before coupling pipe lengths together, clean any debris form the inside of the gasket is zy board, or wooden blocks placed end to end to afford ease of coupling. (2) Places an open, greased coupling under the point where the pipes will meet. Note: Turn the coupling under the point where the pipes gaskets). (3) Slides a dirt-free, greased gasket flaps (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (7) Closes the coupling and seats it in the bottom grooves of the pipeline. (7) Closes the coupling and seats it in the bottom grooves of the pipes. (7) Closes the coupling and seats it in the bottom grooves of the pipeline. (8) Inster the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. 1 Drives in anchors after correct alignment on joins and couplings has been verified. 4 Drives in anchors after correct alignment on joins and couplings has been verified. 4 Drives in anchors after correct alignment on gints and couplings has been verified. 4 Drives in anchors after correct alig	b. The crew places pipe sections in line, end to end, with a gasket and coupling at each point where pipe sections meet.			
	c. The crew unloads an extra tubing section for every 50-75 pieces.			
Note: Valves are normally downloaded right before they are needed in order to avoid them sitting exposed and becoming contaminated with dirt or debris. • et a. The crew places elbows and sticks of pipe to account for terrain conditions, directional changes and expansion loops. • 6. The element conducts coupling operations. • 6. The element conducts coupling trew inspects the pipe sections, couplings and gaskets for cleanliness and serviceability. Note: Keep pipes, valves and vents clean and free from debris during construction. Small quantities of loose material in each pipe length can accumulate in bold gam draps or strainers located at the pumping stations. Before coupling pipe lengths together, clean any debris from the niside and from the pipe ends. Do not use damaged or corrded pipes. • 1. The pipeline coupling crew couples the pipeline.	+ d. The crew places check valves, gate valves and vents at the specified locations along the trace.			
+ e. The crew places elbows and sticks of pipe to account for terrain conditions, directional changes and expansion loops. + e. The pipeline coupling operations. + a. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and serviceability. Note: Keep pipes, valves and vents clean and free from debris during construction. Small quantities of loose material in each pipe length can accumulate in sufficient volume to lodg sand traps or strainers located at the pumping stations. Before coupling pipe lengths together, clean any debris from the inside and from the pipe ends. Do not use damaged or corroded pipes. + b. The pipeline coupling crew couples the pipeline. (1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling. (2) Places an open, greased coupling under the point where the pipes will meet. Note: Turn the coupling unward to prevent exposure to debris. (3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 1. The element installs pipeline suptorts and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Monitors s	Note: Valves are normally downloaded right before they are needed in order to avoid them sitting e or debris.	exposed and be	ecoming contami	nated with dirt
+ 6. The element conducts coupling operations. + a. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and close material in each pipe length can accumulate in sufficient volume to log sand traps or strainers located at the pumping stations. Before coupling pipe lengths cate any debris form the inside and from the pipe ends. Do not use damaged or corroded pipes. + b. The pipeline coupling crew couples the pipeline. (1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling. (2) Places an open, greased coupling under the point where the pipes will meet. Note: Turn the coupling queward to prevent exposure to debris. (3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket laps (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe line into receivers and launchers after they have been permanently placed and anchored. a. Manages testing operations with an observer or representative from the responsible quartermaster to into the stections, ensuring all facilities are tested.	+ e. The crew places elbows and sticks of pipe to account for terrain conditions, directional changes and expansion loops.			
+ a. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and serviceability. Image: Clean Cle	+ 6. The element conducts coupling operations.			
Note: Keep pipes, valves and vents clean and free from debris during construction. Sendl quantities of loose material in each pipe length can any debris from the inside and from the pipe ends. Do not use damaged or corroded pipes. + b. The pipeline coupling grew couples the pipeline.	+ a. The pipeline coupling crew inspects the pipe sections, couplings and gaskets for cleanliness and serviceability.			
+ b. The pipeline coupling crew couples the pipeline. (1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling. (2) Places an open, greased coupling under the point where the pipes will meet.	Note: Keep pipes, valves and vents clean and free from debris during construction. Small quantitie accumulate in sufficient volume to clog sand traps or strainers located at the pumping stations. Before cou from the inside and from the pipe ends. Do not use damaged or corroded pipes.	s of loose mate pling pipe leng	erial in each pipe ths together, cle	length can an any debris
(1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling. (2) Places an open, greased coupling under the point where the pipes will meet. Note: Turn the coupling upward to prevent exposure to debris. (3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets). Note: Do not fold the inside of the gasket flaps (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges.	+ b. The pipeline coupling crew couples the pipeline.			
(2) Places an open, greased coupling under the point where the pipes will meet.	(1) Positions and aligns pipes using pipe jacks, lazy board, or wooden blocks placed end to end to afford ease of coupling.			
Note: Turn the coupling upward to prevent exposure to debris. (3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets). Note: Do not fold the inside of the gasket flaps (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element performs a hydrostatic test of the pipeline. a. Mnaages testing operations with an observer or representative from the responsible quartermaster unit. + 0. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks the accuracy of gauges. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	(2) Places an open, greased coupling under the point where the pipes will meet.			
(3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets). Note: Do not fold the inside of the gasket flaps (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 0. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (2) Checks the accuracy of gauges. (3) Ensure	Note: Turn the coupling upward to prevent exposure to debris.		•	
Note: Do not fold the inside of the gasket flaps (for one-piece gaskets). (4) Aligns and joins the ends of both pipe sections together. (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Drivides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand. <td>(3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets).</td> <td></td> <td></td> <td></td>	(3) Slides a dirt-free, greased gasket onto one pipe end (for one-piece gaskets).			
(4) Aligns and joins the ends of both pipe sections together.	Note: Do not fold the inside of the gasket flaps (for one-piece gaskets).			
 (5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets). (6) Lifts up the coupling and seats it into the bottom grooves of the pipes. (7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand. 	(4) Aligns and joins the ends of both pipe sections together.			
(6) Lifts up the coupling and seats it into the bottom grooves of the pipes.	(5) Slides the gasket over the seam where both pipe ends meet (for one-piece gaskets).			
(7) Closes the coupling halves together completely. (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline.	(6) Lifts up the coupling and seats it into the bottom grooves of the pipes.			
 (8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place. Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand. 	(7) Closes the coupling halves together completely.			
Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwise, a sparkles brass hammer is required. + 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	(8) Inserts the retaining pin into the closed hinge of the snap-joint coupling by driving it into place.			
+ 7. The element installs pipeline supports and anchors. + a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	Note: A 3 pound ball peen hammer can be used for this step if no fuel is in the pipeline; otherwi	se, a sparkles	brass hammer is	required.
+ a. Drives in anchors after correct alignment on joints and couplings has been verified. + b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored. 8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. + 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	+ 7. The element installs pipeline supports and anchors.			•
+ b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored.	+ a. Drives in anchors after correct alignment on joints and couplings has been verified.			
8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging yard. 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible b. Monitors safety. c. Divides the pipeline into test sections, ensuring all facilities are tested. d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand. a. debris and returns them to a. debris and returns them to a. debris and returns them to a. Manages testing operations with an observer or representative from the responsible a. Manages testing operations with an observer or representative from the responsible a. Monitors safety. b. Monitors safety. c. Divides the pipeline into test sections, ensuring all facilities are tested. d. determine the section is the pipeline into test section is the pipeline into test section is the pipeline test of the pipeline into test section is the pipeline test of test	+ b. Couples pipeline into receivers and launchers after they have been permanently placed and anchored.			
+ 9. The element performs a hydrostatic test of the pipeline. a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	8. The element retrieves any unused portions of pipe, pipe end caps, and debris and returns them to the pipe staging vard.			
a. Manages testing operations with an observer or representative from the responsible quartermaster unit. + b. Monitors safety. + c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	+ 9. The element performs a hydrostatic test of the pipeline.			
+ b. Monitors safety.	a. Manages testing operations with an observer or representative from the responsible quartermaster unit.			
+ c. Divides the pipeline into test sections, ensuring all facilities are tested. + d. Sets up testing precautions. (1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	+ b. Monitors safety.			
+ d. Sets up testing precautions.	+ c. Divides the pipeline into test sections, ensuring all facilities are tested			
(1) Checks communications. (2) Checks the accuracy of gauges. (3) Ensures that repair clamps are on hand.	+ d. Sets up testing precautions.		1	
(2) Checks the accuracy of gauges.	(1) Checks communications		1	
(3) Ensures that repair clamps are on hand.	(2) Checks the accuracy of gauges		1	
	(3) Ensures that repair clamps are on hand.			

(4) Coordinates placement of firefighting equipment and crews on site for duration of the test.

(5) Places a tanker vehicle and drums on standby to drain a section of line.

(6) Ensures that shovels and materials to dig and line a pit are at the site in case of a spill.

+ e. Establishes a Prescribed Load List (PLL) for the gaining unit.

+* 10. The element leader submits status reports to higher Headquarters (HQ) according to the unit SOP.

	Task Perfe	ormanc	e Summ	ary Bloo	ck				
Training Un	it				ITER	ATION			
			1		2	;	3	2	1
Date of Training per	· Iteration:								
Day or Night Tra	aining:	Day /	Night	Day	/ Night	Day /	Night	Day /	Night
		#	%	#	%	#	%	#	%
Total Leaders Authorized	% Leaders Present								
Total Soldiers Authorized	% Soldiers Present								
Total Number of Performance Measures	% Performance Measures 'GO'								
Total Number of Critical Performance Measures	% Critical Performance Measures 'GO'								
Live Fire, Total Number of Critical Performance Measures	% Critical Performance Measures 'GO'								
Total Number of Leader Performance Measures	% Leader Performance Measures 'GO'								
MOPP LEVE	EL								
Evaluated Rating per Iteration T, T-, P, P-, U									

Mission(s) supported: None

MOPP 4: Never

MOPP 4 Statement: None

NVG: Never

NVG Statement: None

Prerequisite Collective Task(s):

Step Number	Task Number	Title	Proponent	Status
	05-CO-5250	Perform Construction Operations	05 - Engineers (Collective)	Approved

Supporting Collective Task(s):

Step Number	Task Number	Title	Proponent	Status
1.	71-PLT-5100	Conduct Troop Leading Procedures	71 - Mission Command (Collective)	Approved
2.	05-CO-5001	Perform Project Management	05 - Engineers (Collective)	Approved
2.	05-PLT-5310	Prepare Pipeline Route Profile	05 - Engineers (Collective)	Approved
3.	05-PLT-3006	Establish Work Site Security for a General Engineering Mission	05 - Engineers (Collective)	Approved
5.	05-PLT-5305	Install Underground Pipeline Crossing Site	05 - Engineers (Collective)	Approved
5.	05-PLT-5306	Install Pipeline Pumping Stations	05 - Engineers (Collective)	Approved
6.	05-PLT-5309	Repair a Pipeline	05 - Engineers (Collective)	Approved
7.	05-PLT-5301	Construct Pipeline Suspension Supports	05 - Engineers (Collective)	Approved
7.	05-PLT-5300	Construct Expedient Coupled Pipeline Supports	05 - Engineers (Collective)	Approved
9.	05-PLT-5308	Test Pipeline System	05 - Engineers (Collective)	Approved
10.	05-CO-0018	Conduct Report Procedures	05 - Engineers (Collective)	Approved

OPFOR Task(s):

Task Number	Title	Status
71-CO-8502	OPFOR Execute an Ambush	Approved
71-CO-8504	OPFOR Execute a Reconnaissance Attack	Approved

Supporting Individual Task(s):

Step Number	Task Number	Title	Proponent	Status
	052-120-5100	Develop Base Camp Master Plan	052 - Engineer (Individual)	Approved
	052-120-5107	Plan the Construction of Utility Systems for Non- Permanent Structures	052 - Engineer (Individual)	Approved
	052-12K-1061	Maintain Plumbing Tools	052 - Engineer (Individual)	Approved
	052-12T-3011	Conduct an Engineer Construction Reconnaissance	052 - Engineer (Individual)	Approved
	052-239-3001	Prepare a Bill of Materials	052 - Engineer (Individual)	Approved
	052-239-3029	Schedule Work	052 - Engineer (Individual)	Approved
	052-239-3030	Read Construction Prints	052 - Engineer (Individual)	Approved
	052-239-3036	Supervise the Installation of Pipelines	052 - Engineer (Individual)	Approved
	052-248-1013	Install a Coupled Pipeline	052 - Engineer (Individual)	Approved
	052-248-1014	Repair a Coupled Pipeline	052 - Engineer (Individual)	Approved
	052-248-1016	Install Components With a Pumping Station	052 - Engineer (Individual)	Approved
	052-248-1021	Identify Plumbing Materials	052 - Engineer (Individual)	Approved
	052-248-1040	Interpret Plumbing Prints and Drawings	052 - Engineer (Individual)	Approved
	052-248-1056	Prepare a Plumbing-Materials Takeoff List	052 - Engineer (Individual)	Approved
	052-248-2003	Emplace a Flexible Hose Line	052 - Engineer (Individual)	Approved

Supporting Drill(s): None

Supported AUTL/UJTL Task(s):

Task ID	Title
ART 4.1.7.2.6	Construct Petroleum Distribution Systems

TADSS

TADSS ID	Title	Product Type	Quantity
No TADSS specified			

Equipment (LIN)

LIN	Nomenclature	Qty
W65884	Tool Kit, Supplement, Pipeline Pump Sta, 4, 6, and 8 Inch	1
MC8063	Tool Kit Supplemental, Pipeline C	1

Materiel Items (NSN)

NSN	LIN	Title	Qty
No materiel items specified			

Environment: Environmental protection is not just the law but the right thing to do. It is a continual process and starts with deliberate planning. Always be alert to ways to protect our environment during training and missions. In doing so, you will contribute to the sustainment of our training resources while protecting people and the environment from harmful effects. Refer to the current Environmental Considerations manual and the current GTA Environmental-related Risk Assessment card.

Safety: In a training environment, leaders must perform a risk assessment in accordance with current Risk Management Doctrine. Leaders will complete the current Deliberate Risk Assessment Worksheet in accordance with the TRADOC Safety Officer during the planning and completion of each task and sub-task by assessing mission, enemy, terrain and weather, troops and support available-time available and civil considerations, (METT-TC). Note: During MOPP training, leaders must ensure personnel are monitored for potential heat injury. Local policies and procedures must be followed during times of increased heat category in order to avoid heat related injury. Consider the MOPP work/rest cycles and water replacement guidelines IAW current CBRN doctrine.